Torch TIG

SR 17 Torch

Lightweight and easy to use, these torches offer great manoeuvrability for smooth welding. The molded handle provides optimal grip to achieve the perfect weld. The SR 17 is a real bestseller and is particularly suitable for production work.

FEATURES

BASIC SR 17

Cooling: Air
Capacity:
- direct current (DC): 140 A
- in alternating current (AC): 125 A

Duty cycle: 60%.
Tungsten electrode: Ø 0.5 - 2.4 mm

GRIP SR 17

Cooling: Air
Capacity:
- direct current (DC): 140 A
- in alternating current (AC): 100 A

Duty cycle: 35%.
Tungsten electrode: Ø 0.5 - 2.4 mm

CONFIGURATIONS

				L	DB
				—	GRIP
	Connector		l(m)	Ref	
Ø 10/25		DIN	4 m	—	046009
Ø 35/50			4 m	044449	046030
			8 m	044340	046047
EURO - connector (MIG)			4 m	—	046108

L Trigger

DB Double Button

Included

All the essential consumables for your torch TIG SR17 :

- 2 nozzles (N5 and N7)
- 2 collar supports (Ø1.6 + Ø2/2.4)
- 2 vice pliers (Ø1.6 + Ø2.4)
- 2 caps (1 short + 1 long)
- 2 tungsten electrodes WR2 AC/DC (Ø1.6 + Ø2.4)

• Also available for sale without the torch (ref. 044678)

CONSUMABLES

STANDARD ASSEMBLY

Nozzle

N 4 - Ø 6.5	(x3)	038394
N 5 - Ø 8.0	(x3)	045026
N 6 - Ø 9.5	(x3)	038400
N 7 - Ø 11	(x3)	045033
N 8 - Ø 12.5	(x3)	045286
N 10 - Ø 16	(x3)	045293
N 12 - Ø 19	(x3)	045309

Collar support



Ø 1.6	(x3)	044968
Ø 2.0/2.4	(x3)	044975
Ø 3.2	*(x3)*	*045118*
Ø 4	*(x3)*	*047648*

Standard insulating ring

(x1) 045040

Collet



Ø 1.6	(x3)	044982
Ø 2.0	(x3)	044999
Ø 2.4	(x3)	045019
Ø 3.2	*(x3)*	*045125*
Ø 4	*(x3)*	*047655*

head cover

Courte	(x1)	044944
Longue	(x1)	044951

PRO MOUNTING

Diffuser nozzle

N5 - Ø 8.0	(x3)	045071
N 7 - Ø 11	(x3)	045088

Support for diffuser collar



Ø 1.6	(x2)	045057
Ø 2.0/2.4	(x2)	045064

Insulating ring diffuser

(x1) 045095

Standard insulating ring

(x1) 045040

Collet



Ø 1.6	(x3)	044982
Ø 2.0	(x3)	044999
Ø 2.4	(x3)	045019

head cover

Courte	(x1)	044944
Longue	(x1)	044951

RECOMMANDATIONS

	TIG 160 DC	TIG 168 DC	TIG 200 DC FV	TIG 220 DC FV	TIG 300 DC	TIG 207 AC/DC FV	TIG 208 AC/DC	TIG 220 AC/DC	TIG 250 AC/DC
SR17 connection 10/25 + DIN	_	✓	✓	_	_	_	_	_	_
SR17 connection 35/50 + DIN	✓	✓	✓	_	_	_	_	_	_
SR17 connection EURO	Recommended for MIG/MAG generators with TIG function such as the MULTIPEARL range.								